

MULTI-WIRE SAW

多线切割机YJ-XQB816A

本机器主要用于将切割碳化硅(2"-8")、蓝宝石、水晶、陶瓷、化合物、氧化物、人造宝石、单晶硅等各种硬脆性材料切割分解成片状，可达到提高切割精度，提高工作效率，节省原材料，减少下道工序工作量的目的。

The machine is mainly used for cutting and decomposing various hard and fragile materials such as cutting sapphire (2" -8"), crystal, ceramics, compounds, oxides, artificial gems, single crystal silicon into flakes, which improves the cutting accuracy and working efficiency.



碳化硅衬底



SIC MOSFET

设备特点

- 实现高速切割，切割速度达1500m/min;
- 采用国际先进的伺服系统成套解决方案，系统性能稳定可靠;
- 采用倒挂式摇摆工作台，提高切割效率，支持工作台左右晶相调节;
- 采用伺服电机控制张力大小，可实现张力调节精度达±0.5N;
- 机器表面钣金采用304不锈钢制作，方便清洗维护;
- 切割室和收放线室采用独特密封方式，确保油砂不外漏;
- 采用我司专利断线保护装置，反应灵敏，大幅减小断线后对线网及罗拉的损伤;
- U型导轮布局，采用大规格直径、少数量的导轮布局，导轮数量仅6个;
- 最大加工尺寸为:8"x400mm;
- 收、放线侧均配有伺服电机排线装置，实现双向供线;
- 切割室各门自动化，一键升降，安全便捷。

MAIN TECHNICAL FEATURES

- Achieve high-speed cutting which up to 1500m/min.
- Stable servo system is equipped.
- The down-cut rocking mode workplate increase the cutting efficiency and support to adjust the silicon direction.
- Wire tension is controlled by servo motor. Tension precision is within ± 0.5N.
- The surface sheet metal of the machine is made of 304 stainless steel, which is convenient for cleaning and maintenance.
- Unique sealing methods of the cutting room and wire supply room ensures the oil slurry is not leaking.
- Our patented wire breakage protection device can greatly reduce the damage to the wire and roller after wire break.
- Equipped with 6 pieces of big pulleys.
- The maximum processing size is: 8"x400mm.
- The take-up and pay-off sides are equipped with servo motor cable arrangement to realize bidirectional wire feeding.
- Each door of the cutting room is automated and can be raised and lowered with one click, making it safe and convenient

主要技术参数 MAIN TECHNICAL SPECIFICATIONS

项目/Items	规格/Specs
最大可切断的工件尺寸(Maximum workpiece size)	8"×400mm
外径×线槽宽度(Roller outer dia.*Effective width)	Φ242~252mm×400mm
主轴间距(Spindle spacing)	510mm
钢丝线使用线径(Steel wire diameter)	Φ0.10~Φ0.32mm
钢丝线轴贮线量( Wire storage)	350km×1卷
加速度(Acceleration)	8m/s <sup>2</sup>
切割线速度(Cutting line speed)	1500m/min
工作台升降行程(Table lifting stroke)	240mm
晶体摇摆角度(Ingot rocking angle)	0 ~ ±8°
晶体摇摆速度(Ingot rocking speed)	0-300°/min, 速率可调
切削进给速度(Cutting feed rate)	0.01 ~ 300mm/min
快送进给速度(Fast feed rate)	50 ~ 300mm/min
机器外形尺寸(Size)	长×宽×高 : 3816mm×1828mm×3255mm
机器重量(Weight)	~11000Kg